



DERATED METAL INLINE THREADED .17 WATTS/SQ IN - REDUCES BUILD-UP: SUGGESTED FOR HEAVY SOLUTIONS								
304 STAINLESS MODEL	316L STAINLESS MODEL	TITANIUM MODEL	WATTS	VOLTS	OVERALL LENGTH (IN/MM)	INSERTION LENGTH (IN/MM)	HOT ZONE (IN/MM)	WEIGHT (LB/KG)
WSTO1116 WSTO1216	STO1116 STO1216	TYO1116 TYO1216	1000	120 240	16 / 406	13 / 330	10 / 254	8 / 4
WSTO2125 WSTO2225 WSTO2425	STO2125 STO2225 STO2425	TYO2125 TYO2225 TYO2425	2000	120 240 480	25 / 635	22 / 559	19 / 483	14 / 6
WSTO3235 WSTO3435	STO3235 STO3435	TYO3235 TYO3435	3000	240 480	35 / 889	32 / 813	28 / 711	16 / 7
WSTO4248 WSTO4448	STO4248 STO4448	TYO4248 TYO4448	4000	240 480	48 / 1219	45 / 1143	41 / 1042	19 / 9
WSTO6261 WSTO6461	STO6261 STO6461	TYO6261 TYO6461	6000	240 480	61 / 1549	58 / 1473	55 / 1397	25 / 11